

Specifications

	TOW-BEHIND	TRUCK-MOUNTED
Model	<p style="text-align: center; color: #008000;">ENGINE POWERED</p> <p style="text-align: center;">1550 Smart Control (#85828) 1550 Electronic Control (#85829)</p> <p style="text-align: center; color: #008000;">HYDRAULIC POWERED</p> <p style="text-align: center;">1550 Smart Control (#85824) 1550 Electronic Control (#85825)</p>	<p style="text-align: center; color: black;">TORO, JOHN DEERE & JACOBSEN</p>
Engine	<p style="text-align: center;">Engine Powered: 13 HP Briggs and Stratton Hydraulic Powered: n/a</p>	n/a
Operator Control	<p>Smart: 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control; instant throttle down control (Engine Powered)</p> <p>Electronic: Standard 3-position switch with manual control for spinner and belt speed</p>	<p>Smart: 3-position switch; 4 programmable presets; onboard rate calculator; instantaneous belt and spinner speed control</p> <p>Electronic: Standard 3-position switch with manual control for spinner and belt speed</p>
Empty Weight	<p style="text-align: center;">Engine Powered: 1,324 lbs (601 kg) Hydraulic Powered: 1,021 lbs (463 kg)</p>	710 lbs without mounting kit (322 Kg)
Hopper Capacity	21 ft ³ (0.59 m ³) struck level; 25 ft ³ (0.71 m ³) heaped	
Hopper Size	80" x 36.5" (2.03 x 0.92 m) at the top	
Spreading Width	12' up to 40' (2.7 up to 12 m)	
Spread Application	0.45 ft ³ per 1,000 ft ³ up to 12 ft ³ per 1,000 ft ³ using patented WideSpin Technology	
Topdressing Speed	Up to 8 MPH (12.8 km/h)	
Transport Speed	Up to 8 MPH (12.8 km/h)	
Conveyor Belt	18" (0.46 m) wide pebble surface composition with heavy duty polyester cord	
Metering Gate	Manually operated with Light Spread/Heavy Spread Calibrations	
Drive	<p style="text-align: center;">Engine Powered: Engine Powered Hydraulics Hydraulic Powered: Tow Vehicle Powered Hydraulics</p>	Truck Powered Hydraulics
Wheels	4 Ply 26.5 x 14.00 x 12 Turf	n/a
Warranty	3 years	
Options	<p style="text-align: center;">Trench Filling Attachment (#86150) Cross Conveyor Attachment (#86181)</p>	<p style="text-align: center;">Trench Filling Attachment (#86150) Cross Conveyor Attachment (#86181) Storage Stand (#86197)</p>



Specifications subject to change without notice.