

T3000i/T3100 Daily Preventative Maintenance Checklist

WHAT? Daily Preventative Maintenance for the T3000i/T3100.

Preventative maintenance.

WHY?

Checklist

- □ Clear any fertilizer and debri off of the unit every day with a blower or pressurized air hose. Key areas include:
 - Around the axel (Remove the front hood) (FIGURE 1)
 - o Around and under the engine
 - Inside and under the hopper (Move hopper gate open and closed while cleaning)
 - $\circ \quad \text{Around the transmission} \\$
- Clean with water when necessary (i.e. high humidity days or once a week) WHEN CLEANING WITH WATER BE THOUROUGH ENSURING ALL FERTILIZER IS REMOVED FROM THE UNIT. Water mixed with fertilizer sitting on the unit for extended periods of time is very harmful to any equipment. Blow off the unit with air after cleaning with water.
 - Variable speed pulley Clean the pulley with water as you switch between the wide and narrow setting on the unit. DO NOT USE A LUBRICANT ON THE PULLEY. Blow the water out of the pulley with air when done cleaning. (FIGURE 2)
- □ Check you spray system filter (wear proper personal protective equipment when cleaning the spray system (PPE) Turn the ball valve to off and remove your filter. Clean with water as necessary (Do not use high pressured air or water to clean the filter. It can damage the filter screen). Replace the filter and turn the ball valve back to on. (FIGURE 3)
- □ Check your engine and transmission oil levels



FIGURE 1: Front Hood Removed



FIGURE 2: Variable Speed Pulley



FIGURE 3: Check filter

Date

Completed by:

Serial Number

Name

Signature

This Quick Tip is only a guide, always refer to your Operators Manual